



• Features: Only 18mm thickness, adopting the latest EL lighting panel, no heat generate(cool to touch), lower power consumption & uniform illumination is the most user-friendly lightbox work.


Luminance: On/Off, Flash

Frame: Elegant aluminum case with snap open design

Application: Commercial or signs for shopping mall, shops

& restaurant and offices. Indoor purpose.

© CE certificed.



## **EL Lightbox Specs:**

Size	Case size	Film size	Visible size	Weight
A4	1129X858	1191X842	1146X797	2.5KGS
А3	855X605	837X589	803X555	1.8KGS
A2	431X608	415X590	385X560	1.2KGS
A1	440X314	422X298	395X272	0.7KGS
A0	317X227	299X211X	271X183	0.5KGS

Size unit: mm

## EL panel description:

Brightness: 600lux (150cd/M2)

Illumination: Pink White Input: AC100~240V EL life: about 8,000hours, Half life: about 4,000hours

\*decaying luminescence will start after half life time, and will become dim enough to require EL sheet replacement when reaching life time. No burnout and flashing dark happened as lighting lamp.

\*EL panel for outdoor purpose is open on request, will give special anti-UV and moisture proof.

Inverter: each EL panel will need one inverter to support the illumination work well, and the inverter could keep working well for the new EL panel after replacement.